



METAGLAS® Sight glass for clamp fitting



Applications

- For clamp fittings to
DIN32 676 / ISO 2852

Advantages

- Extremely compact design
- Suitable for food processing and other sterile applications
- Reliability against total failure – the possibility of sudden unexpected rupture is totally excluded
- Fast and simple installation and maintenance
- Extreme resistance to impact and temperature
- Wide acceptance in the European and American food, beverage, pharmaceutical and chemical industries
- Large view

Approvals and technical data

- Pressure Equipment Directive 2014/68/EU, Module H (DIN/EN/ISO 9001)
- AD 2000 Standards W0/TRD 100
- Sight glass fused to metal conforming to DIN 7079
- Borosilicate glass to DIN 7080 / DIN 7079

Material certificates

- Certificate of Conformity to EN 10204-3.1 or 3.2

Operating conditions

- Pressure: -1 to 16 bar
- Temperature: See table

Ring materials	Temperature (TS)
1.4462	-30°C to +280°C
2.4602	-60°C to +300°C

Nominal size		d1	d2	d3	d4	d5	S	S1	D	Max. operating pressure [bar]
DN	Inch									
25/32/40	1", 1 1/2"	50,5	38	33	43,5	34,8	22	10	65	16
50	2"	64	51	45	56,5	47,5	24	12	85	16
65	3"	91	76	65	83,5	72	34	19	125	16
100	4"	119	101	83	110,0	97,4	36	19	160	16
–	5"	144,5	127	95	134,5	123	36	18	180	10
–	6"	167	153	110	156,5	146,8	36	19	210	10
–	8"	217,5	202	140	207,4	198	40	20	280	10